

7" hands-free monitor ART 7/G+/PCM DUAL POE



Reference: ART 7/G+/PCM

Product code: 12310702

EAN code: 8429898020549



Main characteristics

- TCP/IP protocol "G+" digital installation.
- Housing made of white ABS plastic.
- 7" touch screen.
- Hands-free monitor for surface installation.
- High efficiency speakers.
- Connectivity with PCM private call panel.

Dimensions: 222(W) x 154(H) x 15(D) mm.

More information

- Virtual keyboard for call dialing.
- Outdoor panel tracking function.
- Image memory for up to 100 photos (internal storage).
- Automatic image deletion function after 30 days.
- Personalization of background color and ringtones.
- Monitoring of CCTV cameras with ONVIF protocol (up to 32).
- 12Vdc alarm output.
- 4 zones alarm input: PIR, gas sensor, fire...
- Connection via RJ-45 connector.

Visit in the website: <https://www.golmar.es/products/art-7-g-plus-pcm>

Golmar Sistemas de Comunicación S.A.

Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • Fax: +34 934 742 404 • golmar@golmar.es • www.golmar.es

Specifications	
Type of device	Video
Serie	ART
Mounting	Surface
Audio of communication	Hands-free, Full-duplex
Call type	Individual call
Vocal messages	Yes
Available languages	English, Spanish, Portuguese
Ringtones	6
Speaker power (W)	1
Intercom	Inside the apartment, All the installation
Units in parallel (max.)	6
Remote Access / App	Web
Operation	Touch Screen
Inductive loop	No
Guidance LEDs	Yes
Size (inches)	7
Resolution	800x480 px
Minimum illumination (lux)	250
Response time (ms.)	25
Number of colors (Mill.)	16.7
Video format	HDTV I
Format / Video Compression	H.264
Log of calls	Yes
Management software	Yes
Programming	Computer, From the own device
HW platform	Linux
Protocols	TCP / IP
Internal storage	100 images
Memory Image	Yes
Volume settings.	1
Input voltage (V)	12Vcc, PoE, 18Vcc
Requires additional feeder	No
Rest consumption (W)	2.2
Max. consumption (W)	4.2
Installation	UTP
Max. (M)	100
Compatibility	ONVIF, Golmar, IP SIP, VoIP
Technology	IP G +
Functions	Do not disturb, Call to concierge, Date - On-screen, Auto start, Dr. Function, Access control, Lift control
I/O Alarms or Control	4 alarm inputs
Inputs	HZ, PCM
Outputs	Auxiliary ringer, 12Vdc, PCM
Removable connectors	No
Built-in microphone	Yes
Microphone sensitivity (DB)	40
Degree of protection (IP)	30
Relative humidity work (max.)	90
Relative humidity Work (min.)	10
Maximum working temperature (°C)	40
Minimum working temperature (°C)	-10
Mounting frame included	Yes
Material	ABS plastic
Dimensions - Width (mm)	222
Dimensions - High (mm)	154
Dimensions - Deep (mm)	15
Colour	White
Weight (gr.)	470

Accessories

- PCM/G+ single line call panel
- SOB-UNI table stand
- MAC-M3-UNI replacement frame
- HRF-12/1, 25A local power supply for monitors G+

Visit in the website: <https://www.golmar.es/products/art-7-g-plus-pcm>

Visit in the website: <https://www.golmar.es/products/art-7-g-plus-pcm>